

# nifty

# 170

## TRAILER MOUNTED ACCESS PLATFORM



**17.10m (56ft 1in)**  
Working height

**8.70m (28ft 7in)**  
Working outreach

**Telescopic Upper Boom**  
Greater accuracy when  
positioning platform

**Hydraulic Outriggers**  
For quick & easy setup

**Fully Proportional  
Hydraulic Controls**  
Simple, reliable &  
easy to maintain

**Bi-Energy Available**  
Optimising utilisation



[niftylift.com](http://niftylift.com)



# nifty 170

With one of the largest working envelopes in its class the **Nifty 170** delivers maximum reach with stability and control. Octagonal boom sections provide strength without compromising on weight and the telescopic upper boom improves accuracy when positioning the platform. Hydraulically operated outriggers and controls make setting up and operating quick and easy, especially on uneven surfaces.

## SAFETY FEATURES

- Pressure Sensitive Outriggers
- Audible and Visible Alarms
- Manual Recovery with Hand Pump
- Dual Controls (Platform & Base)
- Lock Valves on all Hydraulic Cylinders
- Overrun Brakes with Gas Spring Hand Brake
- Dual Harness Points
- CE Marked



The **170's** outstanding reach Also available on a self-drivable 2x4 or makes it ideal for a wide 4x4 base, the Nifty **170SD**. range of applications.





Fully proportional hydraulic outriggers make setting up and levelling quick and easy even on gradients.

## SPECIFICATIONS

<b>Working Height</b>	17.10m	56ft 1in
<b>Platform Height</b>	15.10m	49ft 6in
<b>Working Outreach</b>	8.70m	28ft 6in
<b>Slew</b>	360°	
<b>Width - Travelling</b>	1.65m	5ft 5in 14ft
<b>- Working</b>	4.40m	5in
<b>Height</b>	2.15m	7ft
<b>Length</b>	6.20m	20ft 4in
<b>Weight</b>	1,900kg*	4,200lbs*
<b>Platform Rotation**</b>	100°	
<b>Platform Capacity</b>	200kg	440lbs
<b>Platform Size</b>	1.10m x 0.65m	3ft 7in x 2ft 2in
<b>Control System</b>	Fully Proportional Hydraulic	
<b>Power System</b>	Mains Only Battery Only Petrol or Diesel Only Bi-Energy (Engine & Battery)	
<b>Drive Option</b>	Traction Drive	

\* Weights may vary according to specification / power options, please confirm before ordering.

\*\* Option Available on request.



Due to a policy of continuing development and improvement, Niftylift reserves the right to change any specification without notice. Please confirm exact specification before ordering.

Supplied by:

**Manufacturers of trailer mounted, self propelled and vehicle mounted platforms.**

